# Burr, Lomax, Pareto, and Logistic Distributions from Ultrasound Speckle

Ultrasonic Imaging 2020, Vol. 42(4-5) 203–212 © The Author(s) 2020 Article reuse guidelines: sagepub.com/journals-permissions DOI: 10.1177/0161734620930621 journals.sagepub.com/home/uix



Kevin J. Parker<sup>1</sup> and Sedigheh S. Poul<sup>2</sup>

#### Abstract

After 100 years of theoretical treatment of speckle patterns from coherent illumination, there remain some open questions about the nature of ultrasound speckle from soft vascularized tissues. A recent hypothesis is that the fractal branching vasculature is responsible for the dominant echo pattern from organs such as the liver. In that case, an analysis of cylindrical scattering structures arranged across a power law distribution of sizes is warranted. Using a simple model of echo strength and basic transformation rules from probability, we derive the first order statistics of speckle considering the amplitude, the intensity, and the natural log of amplitude. The results are given by long tailed distributions that have been studied in the statistics literature for other fields. Examples are given from simulations and animal studies, and the theoretical fit to these preliminary data support the overall framework as a plausible model for characterizing ultrasound speckle statistics.

#### Keywords

ultrasound, speckle, pulse-echo, fractal, vasculature

# Introduction

The study of speckle as a random interference phenomenon from coherent illumination is over 100 years old. The early work in light (predating the laser) utilized prisms to select a narrow band and study scattering,<sup>1</sup> but even at that time the author said, "The theme of our investigation is an old one." With the advent of radar and laser sources, the research on the mathematical properties of optical speckle were accelerated.<sup>2-8</sup> In medical ultrasound, the mathematical treatment of speckle patterns is over 40 years in extent<sup>9</sup> and has developed into a rich set of models for the statistics of backscattered echoes from tissues.<sup>10</sup>

For much of medical ultrasound, important goals include the differentiation of normal versus pathological tissues, the detection of lesions, and the post-processing of B-scans for improved rendering of images including computer assisted diagnosis by algorithms. All of these tasks are strengthened by a careful analysis of speckle or texture from scatterers within normal soft tissues, and then any changes associated with pathological conditions. Accordingly, over time a number of models of ultrasound speckle have been postulated, and many of these models have been adapted from earlier work from optics and electromagnetics. These models include the classical Rayleigh distribution,<sup>9,11-13</sup> the K-distribution,<sup>14-16</sup> a Rician distribution,<sup>6,17,18</sup> the Nakagami distribution,<sup>19-21</sup> a "marked model" distribution,<sup>22,23</sup> and other advanced models<sup>24,25</sup> with continuing applications to a variety of clinical targets.<sup>26-29</sup>

Recently, we have proposed an alternative approach to the first and second order statistics of speckle from soft vascularized tissues.<sup>30-32</sup> Essentially, this model postulates that the fractal branching vasculature and fluid channels have an acoustic impedance mismatch of approximately 3% with respect to the surrounding tissue parenchyma. This mismatch forms the dominant set of inhomogeneities in normal soft vascularized tissues such as the prostate, thyroid, liver, and brain, and therefore the canonical scattering element is a cylinder, not a point or a sphere. Given the multi-scale, fractal structure of the vasculature, an ensemble average over all sizes from large to small leads to power law functions which propagate through different transfer functions and probability density functions (PDFs). This paper examines the first order statistics of speckle from tissue under the assumptions inherent in the framework where weak (Born approximation) scattering originates from a fractal branching set of cylindrical vessels within a reference medium and interrogated by a bandpass ultrasound pulse. It is shown that the echo amplitude, intensity, and log

<sup>1</sup>Department of Electrical and Computer Engineering, University of Rochester, Rochester, NY, USA

#### **Corresponding Author:**

<sup>&</sup>lt;sup>2</sup>Department of Mechanical Engineering, University of Rochester, Rochester, NY, USA

Kevin J. Parker, Department of Electrical and Computer Engineering, University of Rochester, 724 Computer Studies Building, Box 270231, Rochester, NY 14727-0231, USA. Email: kevin.parker@rochester.edu



Figure 1. Model of 3D convolution of a pulse with the fractal branching cylindrical fluid-filled channels in a soft tissue.

amplitude histograms can be modeled by conventional PDFs that are known in the statistics literature, and therefore have well described properties. These all contain a power law parameter that originates from the tissue structure itself. Preliminary examples from a 3D wave simulation of scattering and an animal imaging study of the liver are given to demonstrate the relevance of these functions.

# Theory

# Spatial Convolutions and Transforms

The key assumptions and formulas used in deriving the first order statistics of speckle from a fractal branching vasculature are summarized below. First, we assume that a bandpass pressure pulse P propagating in the x direction with velocity c can be approximated by separable functions<sup>33</sup>:

$$P\left(y,z,t-\frac{x}{c}\right) = G_y\left(y,\sigma_y\right)G_z\left(z,\sigma_z\right)P_x\left(t-\frac{x}{c}\right),\qquad(1)$$

where  $G_y(y,\sigma_y)$  is a Gaussian-shaped transverse beampattern in the *y*-direction with  $\sigma_y$  representing the width parameter, similar for  $G_z(y,\sigma_z)$ , and  $P_x$  is the propagating bandpass pulse shape in the *x*-direction.

Next, applying a 3D convolution model,<sup>33-35</sup> we assess the *dominant* echoes from the pulse interacting with each generation of elements in a branching, fractal, self-similar set of vessels shown in Figure 1, and whose number density as a function of radius *a* follows a power law behavior<sup>36</sup>  $N(a) = N_0/a^b$ , where *b* is a real number greater than 1 defining the branching behavior of the fractal vascular tree and  $N_0$  is a constant determining the overall number density.

The canonical scatterer shape for any branch is a long fluid-filled cylinder of radius a with long axis aligned along the z-direction:

$$f(r) = \begin{cases} \kappa_0 & r \le a \\ 0 & r > a \end{cases}$$

$$F(\rho) = \frac{\kappa_0 \cdot a \cdot J_1 [2\pi a \cdot \rho]}{\rho},$$
(2)

where  $\kappa_0$  is the fractional variation in compressibility, assumed to be  $\ll 1$  consistent with the Born formulation,  $F(\rho)$  represents the Hankel transform using Bracewell's convention,<sup>37</sup> which is the 2D Fourier transform of the radially symmetric function f(r),  $J_1[\cdot]$  is a Bessel function of the first kind of order 1, and  $\rho$  is the spatial frequency equal to  $\sqrt{k_x^2 + k_y^2}$ . The fractional variation in compressibility,  $\kappa_0$ , between blood vessels and liver parenchyma has been estimated to be approximately 0.03, or a 3% difference based on published data.<sup>31</sup>

In addition, we also consider a "soft-walled" cylindrical vessel representing a less sharp transition in acoustic impedance between the fluid interior and the outer "solid" tissue:

$$f(r) = \frac{\kappa_0 \mathbf{e}^{-2\pi \sqrt{\left(\frac{r}{a}\right)^2 + 1}}}{\sqrt{\left(\frac{r}{a}\right)^2 + 1}} \text{ for } r > 0 \text{ and } a > 0.$$
(3)

Its Hankel transform is given by theorem 8.2.24 of Erdélyi and Bateman<sup>38</sup>:

$$F(\rho) = \frac{\kappa_0 a^2 \mathbf{e}^{-2\pi \sqrt{(a\rho)^2 + 1}}}{2\pi \sqrt{(a\rho)^2 + 1}} \text{ for } \rho > 0 \text{ and } a > 0.$$
(4)

The convolution of the pulse with a cylinder of radius a is dominated by the case where the cylinder is perpendicular to the direction of the forward propagating pulse, the x-axis in our case. Thus, assuming an optimal alignment, the 3D convolution result is given by the product of the transforms:

$${}^{3D} \Im \{ \operatorname{echo}(x, y, z) \} = \Im^{3D} \{ p(x, y, z) \} \bullet (k_x)^2$$

$$\bullet \Im^{3D} \{ \operatorname{cylinder}(x, y, z) \},$$
(5)

where the  $(k_x)^2$  term pre-multiplying the cylinder transform stems from the Laplacian spatial derivative in the Born scattering formulation<sup>39,40</sup> and in the 3D convolution model.<sup>35,41</sup>

By Parseval's theorem, the integral of the square of the transform equals the integral of the square of the echo, and provides a measure of the energy within the echo:

$$\iiint \left\{ \operatorname{echo}(x, y, z) \right\}^{2} dx dy dz = \\ \kappa_{0}^{2} \int_{kx=-\infty}^{\infty} \int_{ky=-\infty}^{\infty} \int_{kz=-\infty}^{\infty} \left( \mathfrak{I}^{3D} \left\{ p(x, y, z) \right\} \right)^{2} \bullet \left( k_{x}^{2} \right)^{2} \quad (6) \\ \bullet \left( \mathfrak{I}^{3D} \left\{ \operatorname{cylinder}(x, y, z) \right\} \right)^{2} dk_{x} dk_{y} dk_{z}.$$

We assume the left side of Equation (6) is also proportional to the average intensity I of the echo as a function of the deterministic parameters on the right side, and the square root of this is proportional to the amplitude of the echo. From numerical evaluations of Equation (6) using either of two cylinders (Equations 2 or 3) and either of two bandpass pulses (Gaussian Hermite or hyperbolic secant) we found<sup>32</sup> an approximation which will be useful for deriving a closed form solution of the echo amplitude A,  $A[a] = A_0 \sqrt{a - a_{\min}}$ for  $a > a_{\min}$ , and 0 otherwise. This approximate relationship is justified by the nearly linear increase in the energy term above some minimum threshold, and the asymptotic modulus of  $J_1(ak)$  which is proportional<sup>42</sup> to  $\sqrt{2/(\pi ak)}$  as akbecomes large. The exact shape is dependent on the particular pulse shape's spectrum and the beampattern.

So as a working approximation, we apply the relation  $A[a] = A_0 \sqrt{a - a_{\min}}$  (or for intensity I,  $I[a] = I_0 (a - a_{\min})$ ) for  $a > a_{\min}$ . The parameter  $a_{\min}$  depends on a number of factors, including the dynamic range selected (e.g., 45 dB) and the Rayleigh scattering (long wavelength, small a) behavior of the cylinder interacting with the particular pulse transmit signal, along with the noise floor and quantization floor of the receiver.

### Probability of Amplitudes

Consistent with fractal models,<sup>36,43</sup> we assume that along the line of propagation of the incident pulse in Figure 1, and within the interrogated ensemble, the probability density of encountering vessels at different radii is given by a power law:

$$p(a) = ((b-1)/a_{\min})(a/a_{\min})^{-b}$$
 (7)

for  $a > a_{\min}$  and b > 1, and this will be transformed<sup>44</sup> into the probability distribution of amplitudes, p(A). The general transformation rule is:

$$p[A] = \frac{1}{dA/da} p[a].$$
(8)

In our case, the derivative  $dA/da = \left[ (1/2) A_0 \right] / \sqrt{a - a_{\min}}$ , and the inverse function is  $a[A] = (A/A_0)^2 + a_{\min}$ . Thus, substituting these into Equation (8) the PDF p[A] is:

$$p[A] = \frac{2A(a_{\min})^{b-1}(b-1)}{A_0^2 \left[ \left(\frac{A}{A_0}\right)^2 + a_{\min} \right]^b}.$$
(9)

Furthermore, by substituting  $\lambda = A_0 \sqrt{a_{\min}}$ , we find this reduces to a two-parameter distribution:

$$p[A] = \frac{2A(b-1)}{\lambda^2 \left[ \left(\frac{A}{\lambda}\right)^2 + 1 \right]^b},$$
(10)

which is a Burr Type XII distribution<sup>45,46</sup> with c = 2. Thus, the speckle PDF is given by a two-parameter distribution with known analytic expressions for its cumulative distribution function, and moments.<sup>46</sup> For example, the peak of the distribution occurs at  $A = \lambda/\sqrt{2b-1}$  for b > 1/2.

Thus, the Burr distribution (Equation 10) describes the expected histogram distribution of echo amplitudes from a fractal branching set of Born cylinders. In particular, the power law parameter b is a major parameter of interest.

# Probability of Intensity

For completeness, we examine the PDF of echo intensity from this model. Again, assume that the probability distribution of a fractal branching vasculature is described by a power law in radius a ( $a_{min}$  now pertains to vessel size minimum) as given in Equation (7).

Furthermore, assume the average backscatter intensity  $I(a) \cong I_0(a - a_{\min})$  for  $a > a_{\min}$ , zero otherwise. Then,

$$p_I(I) = \frac{p(a)}{\left(\frac{dI}{da}\right)},\tag{11}$$

where

$$\frac{dI}{da} = I_0; \ a = \left(\frac{I}{I_0}\right) + a_{\min}.$$
 (12)

Thus, using the transformation rules:

$$p_{I}(I) = \frac{\left(\frac{b-1}{a_{\min}}\right)\left(\frac{a}{a_{\min}}\right)^{-b}}{I_{0}} = \frac{(b-1)}{(a_{\min})^{1-b} I_{0} a^{b}} = \frac{(b-1)}{(a_{\min})^{1-b} I_{0} \left(\frac{I}{I_{0}} + a_{\min}\right)^{b}},$$
(13)

which is a Lomax distribution, also related to a Pareto type II distribution.<sup>47</sup> This can be more compactly written as:

$$p_I(I) = \frac{(b-1)\lambda_2^{b-1}}{\left(I + \lambda_2\right)^b} \tag{14}$$

for I > 0 and b > 1, and where  $\lambda_2 = I_0 \cdot a_{\min}$ .

### Probability of Log-Transformed Envelope

In ultrasound imaging, it is conventional to display the echo amplitudes using a log or dB scale to help with visualization of the wide dynamic range. The log transformation affects the distribution, and again using probability transformation rules,<sup>44</sup> let  $y = \ln(A)$ , dy/dA = 1/A, and  $A = e^y$ . Then:

$$p_{y}(y) = \frac{p(A)}{dy/dA} = \frac{2(b-1)\exp[2y]}{\lambda^{2} \left(\frac{\exp[2y]}{\lambda^{2}} + 1\right)^{b}}$$
(15)

for y > 0 and b > 1. Note that in probability literature, this is related to the generalized logistic distribution, and for the special case where  $\lambda = 1$  and b = 2 this becomes the sech<sup>2</sup> distribution.<sup>48</sup>

Thus, each form of the received echoes from speckle (amplitude, intensity, ln[amplitude]) are given by standard PDFs known in the literature (Burr type XII, Lomax, generalized logistic). These have now been derived based on a simple transformation of probability distributions using a mapping function linking vessel radius to echo strength. However, when multiple vessels are present within the interrogating pulse, then more complex treatment is required.

# Increasing Power Law b with Complex Summation

Let us assume that the interrogated sample volume in an imaging system is large enough to encompass two or several discrete cylindrical scatterers simultaneously. Because of the RF modulation of the pulse, their echo amplitudes will be complex. Because of the fractal distribution, the probability distribution of each individual reflected echo amplitude has already been given as a Burr distribution.



**Figure 2.** The vector sum of two independent phasors, pertaining to the real and imaginary parts of a complex addition as is commonly found in models of scattering.

Note that historically, the Rayleigh distribution was derived by considering a complex summation of many independent point scatterers, then by invoking the central limit theorem a Gaussian distribution is generated from the sum of many identical and independent random variables.48-52 In marked contrast in our case, we have cylindrical scatterers from a power law probability distribution over a wide range of radii, and we do not anticipate having so many vessels within a sample volume that we can invoke the central limit theorem. Furthermore, power law distributions (long tail distributions) have slow convergence to the central limit, and so it is instructive to look at the complex sum of two or few scatterers. The statistics literature has derived the sum of random variables of these distributions but the solutions generally involve complicated generalized functions or series.<sup>47,48,53-57</sup> To simplify this, we examine a complex Burr summation.

With reference to Figure 2, using standard notation we can write the amplitude of the complex sum of two phasors A and B as:

$$|C| = \sqrt{\left(|A|\cos\theta_A + |B|\cos\theta_B\right)^2 + \left(|A|\sin\theta_A + |B|\sin\theta_B\right)^2}, (16)$$

where |A| and |B| are independent Burr-distributed amplitudes (sampled from the echoes returning from the fractal branching network), and  $\theta_{A,B}$  are independent and uniformly distributed over  $0 \le \theta < 2\pi$ .

The new random variable  $|A|\cos\theta_A$  is given by the product distribution  $\log^{44,54}$  involving an integral over the PDFs for both |A| and  $\cos\theta_A$ . By the transformation rule we can easily show that if  $p(\theta) = 1/2\pi$  where  $0 \le \theta \le 2\pi$ , then  $p(y = \cos\theta) = 1/(2\pi\sqrt{1-y^2})$  where -1 < y < 1. Then, if  $\hat{A} = |A| \cdot y$ , the product distribution yields:

Measured Signal	PDF	Formula
Echo amplitude A	Burr (XII)	$p(A) = \frac{2A(b-I)}{\lambda^2 \left[ \left(\frac{A}{\lambda}\right)^2 + I \right]^b}$
Echo intensity 1	Lomax (Pareto II)	$p_{I}(I) = \frac{(b-I)\lambda_{2}^{b-I}}{(I+\lambda_{2})^{b}}$
Log intensity $y = \ln(A)$	Generalized logistic (II)	$p_{y}(y) = \frac{2(b-l)\exp[2y]}{\lambda^{2}\left(\frac{\exp[2y]}{\lambda^{2}} + l\right)^{b}}$
Phasor $\hat{A} =  A  \cos \theta_A$	Pearson	$p(\hat{A}) = \frac{(b-l)\Gamma\left(b-\frac{l}{2}\right)}{\sqrt{\pi}\Gamma[b](l+\hat{A}^2)^{b-\frac{l}{2}}}$
Sum of independent components $Z_c = A \cos \theta_A + B \cos \theta_B$	mixed	$p(Z_c) = \frac{4\pi \left(20 + Z_c^2\right)}{\left(4 + Z_c^2\right)^3}$
Fractal distribution of branches radius <i>a</i>	power law (Pareto)	$p(a) = ((b-I)/a_{\min})(a/a_{\min})^{-b}$

$$p(\hat{A}) = \int_{-\infty}^{\infty} p_A(A) p_y\left(\frac{z}{A}\right) \frac{1}{|A|} da$$
$$= \int_{A=z}^{\infty} \frac{4(b-1)}{2\pi \left(A^2+1\right)^b} \sqrt{1-\left(\frac{z}{A}\right)^2} dA$$
$$= \frac{(b-1)\Gamma\left(b-\frac{1}{2}\right)}{\sqrt{\pi}\Gamma[b]\left(1+\hat{A}^2\right)^{b-\frac{1}{2}}}$$
(17)

for b > 1 and  $\lambda = 1$ , where  $\Gamma$  is the gamma function and thus  $p(\hat{A})$  is a double-sided Pearson PDF with  $E[\hat{A}] = 0$ .

Next we need the PDF for  $|A|\cos\theta_A + |B|\cos\theta_B$ . The sum of independent and identically distributed (IID) variables is given by the convolution formula.<sup>44</sup> We found closed form solutions as ratios of polynomials for convolutions of Equation (17) only for integer orders of b-1/2; it is instructive to look at one practical example. Let  $Z_C = Z_A + Z_B$  with a PDF of  $Z_{A,B}$  given by Equation (17), and let b = 2.5. Then we find:

$$p(Z_C) = \frac{4\pi \left(20 + Z_C^2\right)}{\left(4 + Z_C^2\right)^3} = 4\pi \left(\frac{20}{\left(4 + Z_C^2\right)^3} + \frac{Z_C^2}{\left(4 + Z_C^2\right)^3}\right).$$
 (18)

The latter form emphasizes the important term with numerator 20, which dominates for  $Z_C^2 < 20$  and in this example has

denominator power of 3 (or more generally b+1/2) Thus, the PDF of the sum of two Burr phasors' real parts is dominated by an increased power law of b+1/2. In other words, the dominant power law term in the PDFs increases from 2.5 to 3. As more phasors are added, by induction this leading term increases. Specifically, a third phasor  $Z_C$  leads to another convolution of the IID PDFs, raising the denominator power to 4 (or b+3/2). The final PDF of |C| in Equation (16) requires further calculations and becomes complicated, however the trend toward increasing b with increasing number of cylinders is revealed by the examination of the real part of the phasor addition as given above. These PDFs are summarized in Table 1.

#### Methods

#### Simulations

In this study, to make a simple model of the liver parenchyma having vessels with fractal branching nature, a 3D block including multiscale cylindrical branches was generated to simulate the wave propagation and obtain the statistics of speckles. The block dimensions are  $15 \text{ mm} \times 13 \text{ mm} \times 3 \text{ mm}$ in the axial (x), lateral (y), and transverse (z) directions, respectively, with the uniform grid element size of  $69.4 \mu\text{m}$ approximately in all directions. The distribution of the cylindrical branches as scatterers with different radii obeys the power law behavior of Equation (7) with b = 2.5. The cylindrical scatterers' radii ranged from 1 to 6 grid elements, and are randomly distributed in the background with no overlap among any two generated branches.



**Figure 3.** (a) 3D orientation of the transducer and random cylindrical scatterers in the simulation domain. Only a few cylindrical branches are shown here to clarify their orientation as perpendicular to the axial propagation of the interrogating pulse, (b) One realization of a random distribution of weak cylindrical scatterers of various diameters following a power law (fractal) function, and (c) Resulting 4MHz B-scan demonstrating speckle pattern.



**Figure 4.** Histogram curve fitting from speckle in Figure 3: (a) Burr b = 3.357,  $\lambda = 2247$ . Goodness of fit: SSE = 9.879,  $R^2 = 0.995$ , (b) Lomax b = 3.616,  $\lambda = 5.14e + 06$ . Goodness of fit: SSE = 0.009627,  $R^2 = 0.9962$ , and (c) Logistic b = 3.765,  $\lambda = 2494$ , Goodness of fit: SSE = 0.1784,  $R^2 = 0.9949$ .

The k-Wave toolbox in MATLAB (The Mathworks, Inc., Natick, MA, USA) is employed to simulate the propagation of compressional waves in the time domain. This open-source toolbox uses the k-space pseudospectral approach to solve the acoustic wave equations.<sup>58</sup>

Using a virtual linear array transducer defined as the source and sensor in the k-Wave toolbox, an excitation signal is applied in the form of two transient toneburst cycles with a frequency of 4 MHz. This frequency is selected to lie in the common frequency range used for adult human abdominal scanning. For the material properties assignment, the speed of sound is set to 1540 m/s and 1500 m/s for the background and scatterers, respectively, and a uniform density of 1000 kg/m<sup>2</sup> is assumed for the entire medium with a small absorption coefficient. Moreover, in order to avoid the reflection effect

from the boundary, the 3D domain is surrounded by an absorbing boundary layer, known in the k-Wave toolbox as a perfectly matched layer, which absorbs acoustic waves at the boundaries and minimizes reflection back to the domain.

A larger study focused on the effect of the number of scatterers per unit volume from these simulations was recently completed<sup>59</sup> across a range of parameters including 2 < b < 3 and further details of the simulation can be found therein.

#### Liver Scans

Separately, experimental results were obtained from liver experiments. Rat experiments were reviewed and approved by the Institutional Animal Care and Use Committee of



Figure 5. Normal liver B-scan.

Pfizer, Inc., Groton, CT, USA, where the ultrasound RF data were acquired using a Vevo 2100 (VisualSonics, Toronto, ON, Canada) scanner and a 21 MHz center frequency transducer (data provided courtesy of Terry Swanson). For the purpose of examining speckle PDFs, two scans (one normal and one fibrotic) were selected for having good quality B-scan images with adequate liver ROIs. The focal depth was set to 11 mm and positioned to the lower half of the liver in the sagittal plane. In analyzing the results from simulations and liver scans, parameter estimation was performed using MATLAB nonlinear least squares minimization of error, for two-parameter fits of the Burr distribution to the data.

# Results

An example from the simulation results are given in Figure 3. Figure 3(a) shows a 3D orientation of the transducer and random cylindrical scatterers in the domain. Only a few branches are shown here to clarify their orientation as perpendicular to the axial propagation of the interrogating pulse. Figure 3(b) illustrates one realization of a random distribution of weak cylindrical scatterers of various diameters following a power law (fractal) function with b = 2.5 and  $N_0 = 250$ . Figure 3(c) shows the resulting 4MHz B-scan formed from the reflected echoes showing a characteristic speckle pattern.

Figure 4 contains the histograms from left to right of the amplitudes (Burr), intensity (Lomax), and log amplitude (logistic) distributions. In each case, the estimated *b* parameters are near 3.5, higher than the simulated b = 2.5. This is expected since in this simulation the estimated number of cylindrical cross sections per sample volume of the interrogating pulse is near 2.5, so the complex addition of Burr phasors acts to increase the power law above its reference value.

Next, rat livers are examined and ROIs selected within the liver at a depth centered around the transmit focus at 11 mm. Figure 5 provides the B-scan of a normal liver, and Figure 6 illustrates the Burr, Lomax, and logistic fits to the associated histograms. In these cases, the power law parameters are all estimated to be around 3.8. In comparison, a rat liver from the same study but treated with  $CCl_4$  so as to create fibrosis, is shown in Figure 7. The corresponding histograms and theoretical curve fits are shown in Figure 8, and in this case the estimated *b* parameters are not identical but range from 4.5 (Burr) to 4.9 (logistic) with the Lomax estimate intermediate at 4.7. All these *b* estimates are higher than those from normal livers and from the simulations, presumably due to the addition of fibrotic patches into the scattering structures of the liver.

# **Discussion and Conclusion**

There are several key assumptions in the derivation of the PDFs that may limit the applicability of the relationships defined in Table 1. First, the convolution model is only an



**Figure 6.** Normal liver histograms from speckle in Figure 5. (a) Burr b = 3.828,  $\lambda = 396.8$ . Goodness of fit: SSE = 5.749,  $R^2 = 0.9927$ , (b) Lomax b = 3.77,  $\lambda = 1.36e + 05$ . Goodness of fit: SSE = 13.22,  $R^2 = 0.9927$ , and (c) Logistic b = 3.82,  $\lambda = 395.7$ , Goodness of fit: SSE = 0.4592,  $R^2 = 0.9874$ .



Figure 7. Fibrotic liver B-scan.

approximation of the complicated wave propagation, but reasonably so for higher f-number focused beams.<sup>33</sup> Furthermore, the fractal model implicitly assumes normal, soft, isotropic tissue with a simple mapping from cylinders of radius a to echo amplitude A; the relationship is linear in intensity and single-valued over a certain range of radius compared to wavelength. This is a gross approximation, the precise details depend on the exact nature of the bandpass ultrasound pulse, but the simplified function allows straightforward transformation of probabilities. This raises the possibility that more general forms of the Burr distribution (significantly the three-parameter form of the PDF) may be useful and should be investigated further. Also, fractal models are self-similar across a wide range of scales, however any organ will have limits on the largest and smallest vessels. These limits may influence the statistics of speckle depending on the wavelength of the ultrasound pulse employed, and will require additional consideration. Another limitation is that the model

implicitly assumes independent cylindrical scatterers, whereas in reality the branching vasculature is arranged in an orderly manner where each generation originates in a previous generation of vessels. The effect of this on statistics requires further analysis.

The issue of the relative merits of the three main PDFs (Burr, Lomax, and logistic) is a rich area for discussion. Since these have extensive use in the statistics literature, their behaviors are well known in terms of moments, characteristic functions, and estimators of parameters, and a lengthy catalog of these is beyond the scope of the current discussion. However, the long tail inherent in these distributions places them all in a speckle signal-to-noise ratio of less than the Rayleigh 1.91 theoretical mean to standard deviation.<sup>9</sup> In our investigations, using a minimum mean squared error two-parameter curve fit of different data to each of these, we note that the Lomax distribution for intensity was sometimes the outlier with an elevated b estimate compared to others or compared to the baseline value used in simulations. This may be due to the pronounced concentration of the Lomax histogram near the smallest values of intensity (see Figures 4, 6, and 8, middle panel), creating relative insensitivity in the curve fit to the tail of the distribution.

There is an interesting historical twist to these PDFs in that they were originally explored without any reference to ultrasound pulse echo physics. Instead, most of these are associated with economics, income distribution, and complex system lifetimes. The tie between these fields originates with the power law distribution, one of the most ubiquitous laws in natural and human phenomenon.<sup>60</sup> For example in the study of income distribution, a typical country would find many poor people and few rich people. In our ultrasound model, we have many small vessel branches and few large branches. Power law mathematics runs through the core formulas in both fields and then propagates through derived PDFs. Thus, we benefit from the significant work done since



**Figure 8.** Fibrotic liver histograms from speckle in Figure 7. (a) Burr b = 4.467,  $\lambda = 1059$ . Goodness of fit: SSE = 4.15,  $R^2 = 0.9801$ , (b) Lomax b = 4.741,  $\lambda = 1.161e + 06$ . Goodness of fit: SSE = 1.204,  $R^2 = 0.9946$ , and (c) Logistic b = 4.955,  $\lambda = 1148$ , Goodness of fit: SSE = 0.4751,  $R^2 = 0.9881$ .

the 1940s in fields unrelated to ultrasound. The application of these PDFs to scans from a variety of normal and diseased tissues remains for further investigations.

#### Acknowledgments

The authors thank Terri Swanson and Dr. Theresa Tuthill of Pfizer Inc. for providing the RF data from their liver studies. Thanks are also due to Professor Nicholas George for his profound insights on and contributions to speckle theory. The authors are grateful to Dr. R. James White and Gary Ge for the 3D vasculature data set and its rendering.

#### **Declaration of Conflicting Interests**

The author(s) declared no potential conflicts of interest with respect to the research, authorship, and/or publication of this article.

#### Funding

The author(s) disclosed receipt of the following financial support for the research, authorship, and/or publication of this article: This work was supported by National Institutes of Health grant R21EB025290.

#### **ORCID** iD

Kevin J. Parker (D https://orcid.org/0000-0002-6313-6605

#### References

- von Laue M (translated by Lotsch HKV). Sitzungsberichte der Koenig. Pruess Akad Wiss. 1914;47:1144-63.
- George N, Jain A. Speckle in microscopy. Opt Commun. 1972;6(3):253-57.
- George N, Jain A. The wavelength diversity of speckle. Proc SPIE Developments in Laser Technology II. 1974;161-67. Available from https://doi.org/10.1117/12.953849
- George N, Jain A. Space and wavelength dependence of speckle intensity. Appl Phys. 1974;4(3):201-12.
- George N, Jain A, Melville RDS. Speckle, diffusers, and depolarization. Appl Phys. 1975;6(1):65-70.
- Goodman JW. Statistical properties of laser speckle patterns. In: Dainty JC, ed. Laser Speckle and Related Phenomenon. Heidelberg: Springer-Verlag; 1975, pp. 9-75.
- 7. Goodman JW. Some fundamental properties of speckl. J Opt Soc Am. 1976;66(11):1145-50.
- George N, Sinclair DC. Editor's Page: topical issue on laser speckle. J Opt Soc Am. 1976;66(11):1316.
- 9. Burckhardt CB. Speckle in ultrasound b-mode scans. IEEE Trans Sonics Ultrason. 1978;25(1):1-6.
- Thijssen JM. Ultrasonic speckle formation, analysis and processing applied to tissue characterization. Pattern Recogn Lett. 2003;24(4):659-75.
- Wagner RF, Smith SW, Sandrik JM, Lopez H. Statistics of speckle in ultrasound b-scans. IEEE Trans Sonics Ultrason. 1983;30(3):156-63.
- Oosterveld BJ, Thijssen JM, Verhoef WA. Texture of B-mode echograms: 3-D simulations and experiments of the effects of diffraction and scatterer density. Ultrason Imaging. 1985;7(2):142-60.

- Wear KA, Wagner RF, Brown DG, Insana MF. Statistical properties of estimates of signal-to-noise ratio and number of scatterers per resolution cell. J Acoust Soc Am. 1997;102(1):635-41.
- Jakeman E, Tough RJA. Generalized K distribution: a statistical model for weak scattering. J Opt Soc Am A. 1987; 4(9):1764-72.
- Sleefe GE, Lele PP. Tissue characterization based on scatterer number density estimation. IEEE Trans Ultrason Ferroelectr Freq Control. 1988;35(6):749-57.
- Dutt V, Greenleaf JF. Speckle analysis using signal to noise ratios based on fractional order moments. Ultrason Imaging. 1995;17(4):251-68.
- Insana MF, Wagner RF, Garra BS, Brown DG, Shawker TH. Analysis of ultrasound image texture via generalized Rician statistics. Opt Eng. 1986;25(6):743-48.
- Thijssen JM. Echographic image processing. In: Hawkins PW, ed. Advances in Electronics and Electron Physics. Boston: Academic Press; 1992, pp. 317-49.
- Shankar PM. Ultrasonic tissue characterization using a generalized Nakagami model. IEEE Trans Ultrason Ferroelectr Freq Control. 2001;48(6):1716-20.
- Shankar PM. A compound scattering pdf for the ultrasonic echo envelope and its relationship to K and Nakagami distributions. IEEE Trans Ultrason Ferroelectr Freq Control. 2003;50(3):339-43.
- Zhou Z, Tai DI, Wan YL, Tseng JH, Lin YR, Wu S, et al. Hepatic steatosis assessment with ultrasound small-window entropy imaging. Ultrasound Med Biol. 2018;44(7):1327-40.
- Cramblitt RM, Parker KJ. Generation of non-Rayleigh speckle distributions using marked regularity models. IEEE Trans Ultrason Ferroelectr Freq Control. 1999;46(4):867-74.
- Tuthill TA, Sperry RH, Parker KJ. Deviations from Rayleigh statistics in ultrasonic speckle. Ultrason Imaging. 1988;10(2):81-9.
- Prager RW, Gee AH, Treece GM, Berman LH. Analysis of speckle in ultrasound images using fractional order statistics and the homodyned k-distribution. Ultrasonics. 2002;40(1-8): 133-7.
- Yamaguchi T. The quantitative ultrasound diagnosis of liver fibrosis using statistical analysis of the echo envelope. In: Mamou J, Oelze ML, eds. Quantitative Ultrasound in Soft Tissues, Chapter 11. Dordrecht: Springer Netherlands; 2013, pp. 275-88.
- Destrempes F, Cloutier G. A critical review and uniformized representation of statistical distributions modeling the ultrasound echo envelope. Ultrasound Med Biol. 2010;36(7):1037-51.
- Klimonda Z, Karwat P, Piotrzkowska-Wróblewska H, Dobruch-Sobczak K, Litniewski J. Ultrasound scattering statistics predicts the result of neoadjuvant chemotherapy of breast tumors at an early stage of treatment. 2019 IEEE International Ultrasonics Symposium (IUS). 2019:1512-14.
- Tang A, Destrempes F, Kazemirad S, Garcia-Duitama J, Nguyen BN, Cloutier G. Quantitative ultrasound and machine learning for assessment of steatohepatitis in a rat model. Eur Radiol. 2019;29(5):2175-84.
- Hu R, Singla R, Deeba F, Rohling RN. Acoustic shadow detection: study and statistics of B-mode and radiofrequency data. Ultrasound Med Biol. 2019;45(8):2248-57.

- Parker KJ, Carroll-Nellenback JJ, Wood RW. The 3D spatial autocorrelation of the branching fractal vasculature. Acoustics. 2019;1(2):369-81.
- 31. Parker KJ. Shapes and distributions of soft tissue scatterers. Phys Med Biol. 2019;64(17):175022.
- Parker KJ. The first order statistics of backscatter from the fractal branching vasculature. J Acoust Soc Am. 2019;146(5):3318-26.
- Macovski A. Basic Ultrasonic Imaging. Englewood Cliffs, NJ: Prentice-Hall; 1983.
- 34. Prince JL, Links JM. Medical Imaging Signals and Systems. 2nd ed. Boston, MA: Pearson; 2015.
- 35. Bamber JC, Dickinson RJ. Ultrasonic B-scanning: a computer simulation. Phys Med Biol. 1980;25(3):463-79.
- 36. Vicsek T. Fractal Growth Phenomena. 2nd ed. Singapore: World Scientific; 1992.
- Bracewell RN. The Fourier Transform and Its Applications, Chapter 12. New York: McGraw-Hill; 1965.
- Erdélyi A, Bateman H. Tables of Integral Transforms. Vol. 2. New York: McGraw-Hill; 1954.
- Rayleigh L. On the scattering of light spherical shells, and by complete spheres of periodic structure, when the refractivity is small. Proc R Soc Lond A Math Phys Sci. 1918;94(660):296-300.
- 40. Morse PM, Ingard KU. Theoretical Acoustics, Chapter 8. Princeton, NJ: Princeton University Press; 1987.
- 41. Gore JC, Leeman S. Ultrasonic backscattering from human tissue: a realistic model. Phys Med Biol. 1977;22(2):317-26.
- 42. Abramowitz M, Stegun IA. Handbook of Mathematical Functions with Formulas, Graphs, and Mathematical Tables. Washington, DC: U.S. Government Printing Office; 1964.
- Carroll-Nellenback JJ, White RJ, Wood RW, Parker KJ. Liver backscatter and the hepatic vasculature's autocorrelation function. Acoustics. 2020;2(1):3-12.
- Papoulis A. The Fourier Integral and Its Applications. New York: McGraw-Hill; 1987.
- 45. Burr IW. Cumulative frequency functions. Ann Math Stat. 1942;13(2):215-32.

- 46. Rodriguez RN. A guide to the Burr type XII distributions. Biometrika. 1977;64(1):129-34.
- Tahir MH, Cordeiro GM, Mansoor M, Zubair M. The Weibull-Lomax distribution: properties and applications. Hacet J Math Stat. 2015;44(2):455-74.
- Balakrishnan N. Handbook of the Logistic Distribution. New York: Dekker; 1992.
- Middleton D. An Introduction to Statistical Communication Theory. New York: McGraw-Hill; 1960.
- Kluyver JC. A local probability problem. Proc R Neth Acad Arts Sci. 1905;8(1):341-50.
- Greenwood JA, Durand D. The distribution of length and components of the sum of *n* random unit vectors. Ann Math Stat. 1955;26(2):233-46.
- Siddiqui MM. Some problems connected with Rayleigh distributions. J Res Nat Bur Stand D. 1962;66D(2):167-74.
- Nadarajah S. Exponentiated Pareto distributions. Statistics. 2005;39(3):255-60.
- Nadarajah S, Ali MM. Pareto random variables for hydrological modeling. Water Resour Manag. 2008;22(10):1381-93.
- 55. Nadarajah S. Exact distribution of the product of *m* gamma and *n* Pareto random variables. J Comput Appl Math. 2011; 235(15):4496-512.
- Nguyen QH, Robert C. Series expansions for sums of independent Pareto random variables. Lyon; 2013. Available from http://docs.isfa.fr/labo/2012.16.pdf.
- 57. Abu-Dayyeh W, Assrhani A, Ibrahim K. Estimation of the shape and scale parameters of Pareto distribution using ranked set sampling. Stat Papers. 2013;54(1):207-25.
- Treeby BE, Cox BT. k-Wave: MATLAB toolbox for the simulation and reconstruction of photoacoustic wave fields. J Biomed Opt. 2010;15(2):021314.
- Parker KJ, Poul SS. Speckle from branching vasculature: dependence on number density. J Med Imaging. 2020;7(2):027001.
- Newman MEJ. Power laws, Pareto distributions and Zipf's law. Contemp Phys. 2005;46(5):323-51.